

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020744 A1

(51) International Patent Classification⁷: E02D 5/56, 5/80

(21) International Application Number:
PCT/AU2003/001125

(22) International Filing Date:
2 September 2003 (02.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002951386 2 September 2002 (02.09.2002) AU
2002953298 12 December 2002 (12.12.2002) AU

(71) Applicant and

(72) Inventor: FRANCIS, Colln, William [AU/AU]; 22 Rose-
wall Street, Greystanes, NSW 2145 (AU).

(74) Agent: SPRUSON & FERGUSON; GPO Box 3898, Syd-
ney, NSW 2001 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: A PIER



(57) Abstract: A pier (10) to be driven into a ground surface includes an auger member (11) having a shaft (12) that is rotated in a first direction to drive the auger member into the ground surface, and a compaction member (16) having a sleeve (17) surrounding a portion of the shaft. The compaction member (16) includes a compaction part (18) attached to and extending laterally outwardly of the sleeve (17). A threaded rod (23) engages the shaft (12) and is rotated to cause the compaction member (16) to move down the shaft (12) and compact the soil around the shaft.

WO 2004/020744 A1

WO 2004/020744 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A PIER

Technical Field

The present invention relates to piers employed in the building industry but more particularly but not exclusively to a pier that is removable.

Background of the Invention

Many applications in the construction and building industries require the use of a pier to support or maintain the position of a building structure, the structure may be permanent, temporary or may be a plant item. There is also the requirement on occasions for the pier to be removable.

Currently known piers are screwed or driven into a ground surface and are not easily retrieved. These previously known piers also suffer from the disadvantage that as the surrounding soil is disturbed they are not well suited to side loading.

The above problem is addressed by forming a hole and constructing a concrete reinforced pier. This solution is reasonably expensive, with removal of the concrete pier being costly and time consuming.

Previously known piers are described in Australian Patent Applications 72562/91, 19930/95, 69340/98, 91466/98, 74750/81, 44922/96 and 14807/97, as well as International Patent Application PCT/AU98/00782 (WO 99/14441).

Object of the Invention

It is the object of the present invention to overcome or substantially ameliorate at least one of the above discussed disadvantages.

Summary of the Invention

There is disclosed herein a pier to be driven into an earth surface to support a structure to be mounted thereon, said pier including:

an auger member including a shaft that is rotated in a first direction to drive the auger member into the ground surface; and

a soil compaction member to compact soil around the shaft, said compaction member including a sleeve surrounding the shaft and movable relative thereto longitudinally of the shaft, and a transverse part extending laterally from and attached to the sleeve to engage the soil surrounding the shaft so that upon downward movement of the compaction member relative to the shaft soil surrounding the shaft is compacted and wherein

said sleeve is operatively associated with said shaft so that rotation of said compaction member causes rotation of said shaft to thereby drive said auger member.

Preferably the pier includes a drive assembly to move the compaction member relative to the shaft.

5 Preferably said drive assembly includes a threaded rod threadably engaged with said shaft and operatively associated with said compaction member so that upon rotation of said rod said compaction member is caused to move relative to said shaft.

10 Preferably, said drive assembly includes a head attached to an upper portion of said rod and via which said rod is driven, with said nut applying a force to said compaction member to cause said compaction member to move down said shaft.

Preferably, said transverse portion is a plate, with said plate being provided with surfaces they are engaged to cause rotation of said compaction member.

Preferably, said plate is provided with a plurality of apertures which provide said surfaces.

15 Preferably, said plate extends generally normal to said sleeve.

Preferably, said shaft is square or rectangular in transverse cross-section and said sleeve is square or rectangular in transverse cross section so as to be complimentary with respect to said shaft.

Brief Description of the Drawings

20 A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings wherein:

Figure 1 is a schematic isometric view of a pier;

Figure 2 is a schematic side elevation of the pier of Figure 1; and

25 Figure 3 is a schematic side elevation of an insertion tool to be used with the pier of Figures 1 and 2.

Detailed Description of the Preferred Embodiment

30 In the accompanying drawings there is schematically depicted a pier 10. The pier 10 includes an auger member 11 consisting of a shaft 12 to which there is fixed an auger blade 13. The auger blade 13 extends generally longitudinally and angularly with respect to the longitudinal axis 14 of the shaft 12. In this embodiment the auger blade 13 consists of a single convulsion.

The lower end of the shaft is provided with a drill bit 15 which aids penetration of the auger member 11 in a soil surface.

In this embodiment, the shaft 12 is generally square or rectangular in transverse cross-section, however it should be appreciated that the shaft 12 may have alternative configurations.

Operatively associated with the shaft 12 is a soil compaction member 16. The
5 compaction member 16 includes a sleeve 17 that is also square or rectangular configuration so as to be complimentary with respect to the cross-section of the shaft 12. The sleeve 17 surrounds a length of the shaft 12 and is slidable therealong in a longitudinal direction relative to the axis 14.

Attached to the sleeve 17 and extending generally transverse thereof is a
10 compaction part 18, in this embodiment the part 18 is a plate that extends generally normal to the axis 14. Preferably, the compaction part 18 is attached to the sleeve 17 by means of a weld 19.

The compaction part 18 is braced by means of a plurality of flanges or webs 20 that extend between and are attached to the compaction part 18 and sleeve 17.

15 In this embodiment the shaft 12 is hollow and has positioned within it a nut 21. The nut 21 is fixed to the shaft 12 so as to be stationary relative thereto. The nut 21 has a threaded longitudinal passage 22 that is threadably engaged by a threaded rod 23. The rod 23 extends upwardly from the nut 21 through the sleeve 17 to terminate at its upper end with a drive head 23. The drive head 23 bears against a projection of the compaction
20 part 18.

Rotation of the head 23 about the longitudinal axis 14 causes movement of the compaction part 18 relative to the shaft 12 in the direction of the axis 14. In this respect, it should be appreciated that the sleeve 17 slides over the shaft 12.

The compaction part 18 includes a plurality of apertures 26 that provide surfaces
25 25 via which the compaction member 16 is driven about the longitudinal axis 14.

In use of the above described pier 10, the surfaces 25 are engaged so that the compaction member 16 is driven rotationally in the direction of the arrow 27. This rotation of the compaction member 16 drives the auger member 11 so that the shaft 12 enters a ground surface. At a desired depth driving of the shaft 12 ceases. Thereafter the
30 nut 21 is rotatably driven so that the compaction member 16 is moved in the direction of the arrow 28. The compaction part 18 engages the soil surface and compacts the soil surface surrounding the shaft 12.

The pier 10 is removable if so required. To remove the pier 10 the head 23 is rotated in the opposite direction removing the flanges 20 from the soil layer. Thereafter

the surfaces 25 are again engaged and the compaction member rotated in the opposite direction to the arrow 27 to remove the auger member 11.

In Figure 3 there is schematically depicted an insertion tool 30 that is one arrangement of inserting and removing the pier 10 of Figures 1 and 2. The insertion tool
5 30 includes a first drive portion 31 that is to engage the surfaces 25 to cause rotation of the compaction member 16, and a second drive portion 32 that engages the head 23. The portions 31 and 32 are both attached to a driven shaft 33 extending to a gear assembly 34 that is driven by an associated motor.

The drive portion 32 includes a socket 34 that is shaped to engage the head 23 to
10 cause rotation thereof upon rotation of the shaft 33. The socket 34 is attached to the shaft 33 so as to rotate therewith by means of a pin 35.

The drive portion 31 includes a sleeve 36 slidably mounted on the radially outer peripheral surface of the socket 34 so as to be movable relative thereto in the direction of the axis 14. The sleeve 36 has attached to it a flange 37 having a plurality of drive pins
15 38 that enter the apertures 26 to engage the surfaces 25. The pin 35 extends through slots 39 formed in the sleeves 36 which slots 39 extend in the direction of the axis 14 so that the sleeve 36 is slidable in the direction of the axis 14 relative to the socket 34, with the sleeve 36 restricted so as to rotate with the shaft 33.

Preferably, the apertures 26 are of a "key hole" configuration and the pins 38
20 each provided with a head 40.

In operation of the insertion tool 30, preferably the tool 30 is attached to a mobile apparatus that has a vertically movable arm to which the tool 30 is attached. The tool 30 would be attached to the pier 10 by having the pins 38 inserted in the apertures 26 and moved relative thereto so that the pier 10 is attached to the flange 37. Thereafter the
25 pier 10 may be lifted to an appropriate position. Thereafter the shaft 33 is rotatably driven so that the compaction member 16 drives the shaft 12. When the shaft 12 has been driven to an appropriate depth, the pins 38 are removed from within the apertures 26 and the flange 27 raised so that it is no longer operatively associated with the compaction member 16. Thereafter the socket 34 is moved into engagement with the head 23 so that
30 rotation of the shaft 33 will then drive the rod 23 and cause the compaction part 18 to move down the shaft 12 and compact the soil.

When the pier 10 is to be removed the above steps are reversed.

CLAIMS:

1. A pier to be driven into an earth surface to support a structure to be mounted thereon, said pier including:

an auger member including a shaft that is rotated in a first direction to drive the
5 auger member into the ground surface;

a soil compaction member to compact soil around the shaft, said compaction member including a sleeve surrounding the shaft and movable relative thereto longitudinally of the shaft, and a transverse part extending laterally from and attached to the sleeve to engage the soil surrounding the shaft so that upon downward movement of
10 the compaction member relative to the shaft soil surrounding the shaft is compacted; and wherein

said sleeve is operatively associated with said shaft so that rotation of said compaction member causes rotation of said shaft to thereby drive said auger member.

2. The pier of claim 1 wherein, the pier includes a drive assembly to move
15 the compaction member relative to the shaft.

3. The pier of claim 2 wherein, said drive assembly includes a threaded rod threadably engaged with said shaft and operatively associated with said compaction member so that upon rotation of said rod said compaction member is caused to move relative to said shaft.

4. The pier of claim 3 wherein, said drive assembly includes a head
20 attached to an upper portion of said rod and via which said rod is driven, with said nut applying a force to said compaction member to cause said compaction member to move down said shaft.


5. The pier of any one of claim 1 to 4 wherein, said transverse portion is a
25 plate, with said plate being provided with surfaces they are engaged to cause rotation of said compaction member.

6. The pier of claim 5 said plate is provided with a plurality of apertures which provide said surfaces.

7. The pier of claim 6 said plate extends generally normal to said sleeve.

8. The pier of claim 7 said shaft is square or rectangular in transverse
30 cross-section and said sleeve is square or rectangular in transverse cross section so as to be complimentary with respect to said shaft.

9. A pier substantially or hereinbefore described with reference to the accompanying drawings.

FIG. 1

SUBSTITUTE SHEET (Rule 26)

2/3




FIG. 2

3/3




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/01125

A. CLASSIFICATION OF SUBJECT MATTER		
Int. Cl. ⁷ : E02D 5/56, 5/80		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WPAT : E02D 5/56, 5/80 and Keywords (pier+, compact+, soil)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5295766 A (TIKKAINEN) 22 March 1994	
A	US 5234290 A (COLLINS) 10 August 1993	
A	EP 032132 B1 (NAGASHIMA) 21 March 1984	
<input type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 25 September 2003		Date of mailing of the international search report 02 OCT 2003
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No. (02) 6285 3929		Authorized officer S. GHOSH Telephone No : (02) 6283 2163

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/AU03/01125

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member			
US	5295766	AU	72562/91	CA	2075968
		FI	901002	WO	9113225
US	5234290	AU	29013/92	EP	648296
EP	32132	GB	2067621	WO	9309299
					END OF ANNEX